

Material Safety Data Sheet

81BA04-001 BRONZE BA GLAZE

Product and company identification

: 81BA04-001 Code

BRONZE BA GLAZE Synonym

Material uses Coatings: Surface coatings and finishes.

Manufacturer : Chemcraft Coating Technology Inc.

311 Otterson Drive, Suite 60

Chico, CA 95928

Ph:530-894-3585 Fax:530-896-0657

In case of emergency 1-800-424-5571

1/5/2006. Validation date **Print date** 5/31/2006. **Validator** A. Davis

2. Composition/information on ingredients

<u>Name</u>	CAS number	<u>%</u>
Acetone	67-64-1	15 - 30
Isopropanol	67-63-0	5 - 15
Diethylene glycol monomethyl ether	111-77-3	0.1 - 1
N-Methyl pyrrolidone	872-50-4	0.1 - 1
Silica quartz	14808-60-7	0.1 - 1

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

3. Hazards identification

Physical state

Liquid.

OSHAHCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Routes of entry

: Dermal contact. Eye contact. Inhalation. Ingestion.

Effects of Acute

Risk of cancer depends on duration and level of exposure.

Exposure

Potential chronic health effects

: CARCINOGENIC EFFECTS: Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [2-Propanone]. Classified D (Not classifiable for humans or animals.) by EPA [2-Propanone]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [2-Propanol]. Classified 4 (Probably not for humans.) by IARC, None. by OSHA [Titanium dioxide (TiO2)]. Classified 4 (Probably not for humans.) by IARC, None. by OSHA [Ethanol, 2-(2-methoxyethoxy)-]. Classified A5 (Not suspected for humans.) by ACGIH [2-Pyrrolidinone, 1-methyl-]. Classified 1 (Proven for humans.) by IARC, + (Proven.) by OSHA, + (Proven.) by NIOSH [Quartz (SiO2)].

MUTAGENIC EFFECTS: Not available.

TERATOGENIC EFFECTS: Classified None. for humans [2-Propanone]. Teratogenic NOAEL [89 ppm] [2-Pyrrolidinone, 1-methyl-].

Medical conditions aggravated by overexposure

Repeated or prolonged exposure to the substance can produce target organs damage.

See toxicological information (section 11)

5/31/2006. Page: 1/7

^{*} Toxicological information, if available, is listed in section 11

4. First aid measures

Eye contact

: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

Skin contact

: Flush contaminated skin with plenty of water. Continue to rinse for at least 10 minutes. Get medical attention. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation

: Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Ingestion

: Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training.

5. Fire-fighting measures

Flammability of the product

Products of combustion

Extinguishing media

Suitable

Not suitable

Special exposure hazards

Special protective equipment for fire-fighters

Fire Hazards in Presence of Various Substances

: Flammable.

: These products are carbon oxides (CO, CO₂). Some metallic oxides.

- : Use an extinguishing agent suitable for the surrounding fire.
- : None known.
- : No specific hazard.
- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

Non-flammable in the presence of the following materials or conditions: shocks and mechanical impacts, oxidizing materials, reducing materials, combustible materials, organic materials, metals, acids, alkalis and moisture.

Explosion Hazards in Presence of Various Substances

: Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge.

Non-explosive in the presence of the following materials or conditions: heat, shocks and mechanical impacts, oxidizing materials, reducing materials, combustible materials, organic materials, metals, acids, alkalis and moisture.

6. Accidental release measures

Personal precautions

: Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment.

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up

: If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

5/31/2006. Page: 2/7

7. Handling and storage

Handling Storage

- : Wash thoroughly after handling.
- : Keep container tightly closed. Keep container in a cool, well-ventilated area.

8. Exposure controls/personal protection

Consult local authorities for acceptable exposure limits.

Engineering measures

: Use only with adequate ventilation. If user operations generate dust, fumes, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protection



Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and chemical properties

Physical state

: Liquid.

Flash point

pН

: The lowest known value is Closed cup: -18°C (-0.4°F). (T.C.C.). (2-Propanone)

Auto-ignition temperature

The lowest known value is 432°C (809.6°F) (2-Propanol).

Flammable limits

The greatest known range is Lower: 2.6% Upper: 12.8% (2-Propanone)

: Neutral.

Boiling/condensation point

: The lowest known value is 56.2°C (133.2°F) (2-Propanone). Weighted average: 83.93°C (183.1°F)

Melting/freezing point

: May start to solidify at 0°C (32°F) based on data for: Water. Weighted average: -44.53°C (-48.2°F)

Relative density

: Weighted average: 0.92 (Water = 1)

Vapor pressure

: The highest known value is 24.1 kPa (181 mm Hg) (at 20°C) (2-Propanone). Weighted average: 9.02 kPa (67.66 mm Hg) (at 20°C)

The highest known value is 2.1 (Air = 1) (2-Propanol). Weighted average: 1.5 (Air = 1)

Vapor density

: Not dispersible in cold water, hot water.

Dispersibility properties

See solubility in methanol, diethyl ether, n-octanol.

Solubility

: Easily soluble in methanol, diethyl ether. Partially soluble in n-octanol.

Insoluble in cold water, hot water.

5/31/2006. Page: 3/7

10. Stability and reactivity

Stability and reactivity Incompatibility with various substances

- : The product is stable.
- Reactive or incompatible with the following materials: oxidizing materials and acids. Slightly reactive or incompatible with the following materials: reducing materials and alkalis.

Non-reactive or compatible with the following materials: combustible materials, organic materials, metals and moisture.

11. Toxicological information

Toxicity data

Product/ingredient name	<u>Test</u>	<u>Result</u>	Route	Species
2-Propanone	LD50	5800 mg/kg	Oral	Rat
	LD50	3000 mg/kg	Oral	Mouse
	LD50	20000 mg/kg	Dermal	Rabbit.
	LC50	50100 mg/m³ (8 hour/hours)	Inhalation	Rat
	LC50	44000 mg/m ³ (4	Inhalation	Mouse
	2000	hour/hours)	midiation	Modeo
2-Propanol	LD50	5045 mg/kg	Oral	Rat
·	LD50	4797 mg/kg	Oral	Dog
	LD50	3600 mg/kg	Oral	Mouse
	LD50	12800 mg/kg	Dermal	Rabbit
	LC50	16000 ppm (8 hour/hours)	Inhalation	Rat.

Chronic effects on humans

CARCINOGENIC EFFECTS: Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [2-Propanone]. Classified D (Not classifiable for humans or animals.) by EPA [2-Propanone]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [2-Propanol]. Classified 4 (Probably not for humans.) by IARC, None. by OSHA [Titanium dioxide (TiO2)]. Classified 4 (Probably not for humans.) by IARC, None. by OSHA [Ethanol, 2-(2-methoxyethoxy)-]. Classified A5 (Not suspected for humans.) by ACGIH [2-Pyrrolidinone, 1-methyl-]. Classified 1 (Proven for humans.) by IARC, + (Proven.) by OSHA, + (Proven.) by NIOSH [Quartz (SiO2)].

TERATOGENIC EFFECTS: Classified None. for humans [2-Propanone]. Teratogenic NOAEL [89 ppm] [2-Pyrrolidinone, 1-methyl-].

Contains material which causes damage to the following organs: blood, kidneys, lungs, the nervous system, liver.

Other toxic effects on humans

: Hazardous in case of ingestion, of inhalation.

Special remarks on chronic effects on humans

: Detected in maternal milk in human. (2-Propanol)

Special remarks on other toxic effects on humans Specific effects

: Material is irritating to mucous membranes and upper respiratory tract. (2-Propanone)

Carcinogenic effects

: Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenic effects
Teratogenicity /
Reproductive toxicity

No known significant effects or critical hazards.

: No known significant effects or critical hazards.

5/31/2006. Page: 4/7

12. Ecological information

Ecotoxicity data

Canada

Product/ingredient name Species Period Result 2-Pyrrolidinone, 1-methyl-Trout (EC50) 96 hour/hours 5104 mg/l Fathead minnow. (EC50) 96 hour/hours 4518 mg/l Bluegill. (EC50) 96 hour/hours 5656 mg/l Daphnia (LC50) 96 hour/hours 3135 mg/l

Environmental precautions

Octanol/water partition coefficient

: No known significant effects or critical hazards.

: The product is more soluble in octanol.

: Not available.

Bioconcentration factor

Products of degradation

: These products are carbon oxides (CO, CO₂) and water. Some metallic oxides.

: The product itself and its products of degradation are not toxic.

Toxicity of the products of biodegradation

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14.Transport information

Regulatory information	UN number	Class	PG*	Label
TDG Classification	1263PAINT	3	II	<u>&</u>

PG*: Packing group

15. Regulatoryinformation

United States

HCS Classification

: Carcinogen

Target organ effects

U.S. Federal regulations

SARA 302/304/311/312 extremely hazardous substances: Isopropyl alcohol SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: No products were found. SARA 311/312 MSDS distribution - chemical inventory - hazard identification: 2-Propanol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Water Act (CWA) 307: No products were found. Clean Water Act (CWA) 311: No products were found.

5/31/2006. Page: 5/7

15. Regulatoryinformation

Clean Air Act (CAA) 112 accidental release prevention: Ethanol, 2-(2-methoxyethoxy)-;

Ethanol, 2-butoxy-; Aqua-Chem Raw Umber

Clean Air Act (CAA) 112 regulated flammable substances: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

State regulations

WARNING: This product contains chemical/chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.: Quartz (SiO2); Carbon Black; 2-Pyrrolidinone, 1-methyl-

WARNING: This product contains chemical/chemicals known to the state of California to cause birth defects or other reproductive harm.: 2-Pyrrolidinone, 1-methyl-

WARNING: This product contains chemical/chemicals known to the state of California to cause cancer.: Quartz (SiO2); Carbon Black

Pennsylvania RTK: Ethanol, 2-(2-methoxyethoxy)-; Ethanol, 2-butoxy-; Isopropyl alcohol;

2-Pyrrolidinone, 1-methyl-

Florida: 2-Pyrrolidinone, 1-methyl-Minnesota: 2-Pyrrolidinone, 1-methyl-

Massachusetts RTK: Isopropyl alcohol; 2-Pyrrolidinone, 1-methyl-

New Jersey: Ethanol, 2-(2-methoxyethoxy)-; Ethanol, 2-butoxy-; Isopropyl alcohol;

2-Pyrrolidinone, 1-methyl-

TSCA 8(b) inventory: Ethanol, 2-(2-methoxyethoxy)-; Ethanol, 2-butoxy-; Aqua-Chem

Raw Umber; Isopropyl alcohol

SARA 302/304/311/312 extremely hazardous substances: Isopropyl alcohol SARA 311/312 MSDS distribution - chemical inventory - hazard identification:

2-Propanol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health

hazard

CERCLA: Hazardous substances.: 2-Propanone: 5000 lbs. (2268 kg); 2-Pyrrolidinone,

1-methyl-;

Ingredient name	<u>Cancer</u>	<u>Reproductive</u>	No significant risk level	Maximum acceptable dosage level
2-Pyrrolidinone, 1-methyl-	No.	Yes.	No.	No.
Quartz (SiO2)	Yes.	No.	No.	No.
Carbon Black	Yes.	No.	No.	No.

Canada

WHMIS (Canada)

: Class B-2: Flammable liquid

Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

16. Other information

Label requirements

EXTREMELY FLAMMABLE LIQUID AND VAPOR.

VAPOR MAY CAUSE FLASH FIRE.

CANCER HAZARD.

CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS:

BLOOD, KIDNEYS, LUNGS, NERVOUS SYSTEM, LIVER.

5/31/2006. Page: 6/7

16. Other information

Hazardous Material Information System (U.S.A.)



^{*} Indicates may be chronic effects

National Fire Protection Association (U.S.A.)



Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

5/31/2006. Page: 7/7