



Material Safety Data Sheet

825-3705 GLAZE - MEDIUM BROWN

1. Product and company identification

Code : 825-3705
Synonym : GLAZE - MEDIUM BROWN
Material uses : Coatings: Surface coatings and finishes.
Manufacturer : Chemcraft® Coating Technology Inc.
311 Otterson Drive, Suite 60
Chico, CA 95928
Ph:530-894-3585 Fax:530-896-0657
In case of emergency : 1-800-424-5571
Validation date : 4/23/2007.
Print date : 6/22/2007.
Validator : K. DeBiasi

2. Hazardous ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Heavy aromatic naphtha.	64742-94-5	50 - 70
Methanol	67-56-1	1 - 5
Ferric oxide	1309-37-1	0.1 - 1
N-Methyl pyrrolidone	872-50-4	0.1 - 1
Xylenes	1330-20-7	0.1 - 1
Silica quartz	14808-60-7	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

* Toxicological information, if available, is listed in section 11

3. Hazards identification

Physical state : Liquid.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Effects of Acute Exposure : Risk of cancer depends on duration and level of exposure.

Potential chronic health effects : **CARCINOGENIC EFFECTS:** Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [Methanol]. Classified A5 (Not suspected for humans.) by ACGIH [2-Pyrrolidinone, 1-methyl-]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [1-Butanol]. Classified 1 (Proven for humans.) by IARC, + (Proven.) by OSHA, + (Proven.) by NIOSH [Quartz (SiO₂)]. Classified 4 (Probably not for humans.) by IARC, None. by OSHA [Carbon Black].
MUTAGENIC EFFECTS: Not available.
TERATOGENIC EFFECTS: Teratogenic NOAEL [89 ppm] [2-Pyrrolidinone, 1-methyl-].

Medical conditions aggravated by over-exposure : Repeated or prolonged exposure to the substance can produce target organs damage.

See toxicological information (section 11)

4 . First aid measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Skin contact** : Flush contaminated skin with plenty of water. Continue to rinse for at least 10 minutes. Get medical attention. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

5 . Fire-fighting measures

- Flammability of the product** : Flammable.
- Products of combustion** : These products are carbon oxides (CO, CO₂). Some metallic oxides.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : No specific hazard.
- Special Remarks on Fire Hazards** : Container explosion may occur under fire conditions or when heated. Vapor may travel considerable distance to source of ignition and flash back. (Solvent naphtha (petroleum), heavy arom.)
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Fire Hazards in Presence of Various Substances** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
- Explosion Hazards in Presence of Various Substances** : Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge.

6 . Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

7. Handling and storage

- Handling** : Wash thoroughly after handling.
- Storage** : Keep container tightly closed. Keep container in a cool, well-ventilated area.

8. Exposure controls/personal protection

Consult local authorities for acceptable exposure limits.

- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protection



- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : The lowest known value is Closed cup: 12°C (53.6°F). (Tagliabue.). Open cup: 15.6°C (60.1°F). (Tagliabue.). (Methanol)
- Auto-ignition temperature** : The lowest known value is 463.89°C (867°F) (Methanol).
- Flammable limits** : The greatest known range is Lower: 6% Upper: 36.5% (Methanol)
- pH** : Neutral.
- Boiling/condensation point** : The lowest known value is 64.5°C (148.1°F) (Methanol). Weighted average: 173.88°C (345°F)
- Melting/freezing point** : May start to solidify at -73°C (-99.4°F) based on data for: Solvent naphtha (petroleum), heavy arom.. Weighted average: -73.73°C (-100.7°F)
- Relative density** : 1.082 (Water = 1)
- Vapor pressure** : The highest known value is 12.2 kPa (91.8 mm Hg) (at 20°C) (Methanol). Weighted average: 0.37 kPa (2.78 mm Hg) (at 20°C)
- Vapor density** : The highest known value is 4.8 (Air = 1) (Solvent naphtha (petroleum), heavy arom.). Weighted average: 4.69 (Air = 1)
- Evaporation rate** : 0.06 (Solvent naphtha (petroleum), heavy arom.) compared with Butyl acetate.
- Dispersibility properties** : Not dispersible in cold water, hot water.
See solubility in methanol, diethyl ether, n-octanol, acetone.
- Solubility** : Easily soluble in n-octanol, acetone.
Soluble in methanol, diethyl ether.
Insoluble in cold water, hot water.

10 . Stability and reactivity

- Stability and reactivity** : The product is stable.
- Incompatibility with various substances** : Highly reactive or incompatible with the following materials: oxidizing materials.
Reactive or incompatible with the following materials: acids and alkalis.
Slightly reactive or incompatible with the following materials: reducing materials and organic materials.
Non-reactive or compatible with the following materials: combustible materials, metals and moisture.

11 . Toxicological information

Toxicity data

<u>Product/ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Methanol	LD50	6200 mg/kg	Oral	Rat.
	LD50	5600 mg/kg	Oral	Rat
	LD50	15800 mg/kg	Dermal	Rabbit.
	LC50	64000 ppm (4 hour/hours)	Inhalation	Rat.

- Chronic effects on humans** : **CARCINOGENIC EFFECTS:** Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [Methanol]. Classified A5 (Not suspected for humans.) by ACGIH [2-Pyrrolidinone, 1-methyl-]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [1-Butanol]. Classified 1 (Proven for humans.) by IARC, + (Proven.) by OSHA, + (Proven.) by NIOSH [Quartz (SiO₂)]. Classified 4 (Probably not for humans.) by IARC, None. by OSHA [Carbon Black].
TERATOGENIC EFFECTS: Teratogenic NOAEL [89 ppm] [2-Pyrrolidinone, 1-methyl-]. Contains material which causes damage to the following organs: blood, kidneys, lungs, the nervous system, liver.

- Other toxic effects on humans** : Very hazardous in case of inhalation.
Hazardous in case of ingestion.
Slightly hazardous in case of skin contact (permeator).

- Special remarks on chronic effects on humans** : May be fatal or cause blindness if swallowed. Animal: embryotoxic, passes through the placental barrier. (Methanol)

- Special remarks on other toxic effects on humans** : Material is irritating to mucous membranes and upper respiratory tract. (Solvent naphtha (petroleum), heavy arom.)

Specific effects

- Carcinogenic effects** : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenic effects** : No known significant effects or critical hazards.
- Teratogenicity / Reproductive toxicity** : No known significant effects or critical hazards.

12 . Ecological information

Ecotoxicity data

Canada

<u>Product/ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
2-Pyrrolidinone, 1-methyl-	Trout (EC50)	96 hour/hours	5104 mg/l
	Fathead minnow. (EC50)	96 hour/hours	4518 mg/l
	Bluegill. (EC50)	96 hour/hours	5656 mg/l
	Daphnia (LC50)	96 hour/hours	3135 mg/l

- Environmental precautions** : No known significant effects or critical hazards.

- Octanol/water partition coefficient** : The product is much more soluble in octanol.

- Bioconcentration factor** : Not available.

12 . Ecological information

- Products of degradation** : These products are carbon oxides (CO, CO₂) and water. Some metallic oxides.
- Toxicity of the products of biodegradation** : The product itself and its products of degradation are not toxic.

13 . Disposal considerations


- Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14 . Transport information

Regulatory information	UN number	Class	PG*	Label
TDG Classification	1263 PAINT	3	II	

PG* : Packing group

15 . Regulatory information

United States

- HCS Classification** : Carcinogen
Target organ effects
- U.S. Federal regulations** : SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: Methanol
SARA 311/312 MSDS distribution - chemical inventory - hazard identification: No products were found.
Clean Water Act (CWA) 307: Benzene, ethyl-
Clean Water Act (CWA) 311: No products were found.
Clean Air Act (CAA) 112 accidental release prevention: No products were found.
Clean Air Act (CAA) 112 regulated flammable substances: No products were found.
Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

State regulations

- WARNING:** This product contains chemical/chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.: Van-Sol 63/Apsol #2/Vansol 63/Hisol 10; Quartz (SiO₂); 2-Pyrrolidinone, 1-methyl-; Benzene, methyl-; Carbon Black
- WARNING:** This product contains chemical/chemicals known to the state of California to cause birth defects or other reproductive harm.: 2-Pyrrolidinone, 1-methyl-; Benzene, methyl-
- WARNING:** This product contains chemical/chemicals known to the state of California to cause cancer.: Quartz (SiO₂); Carbon Black
- Illinois toxic substances disclosure to employee act: Benzene, ethyl-
New York release reporting list: Methanol; Acetic Acid, Butyl Ester
New York acutely hazardous substances: Benzene, ethyl-

15. Regulatory information

Rhode Island RTK hazardous substances: Benzene, ethyl-; Methanol
 Pennsylvania RTK: Benzene, ethyl-; Benzene, dimethyl-; 1,2-Propanediol; Methanol: (environmental hazard); 2-Pyrrolidinone, 1-methyl-; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester; Benzene, methyl-
 Florida: Benzene, ethyl-; Methanol; 2-Pyrrolidinone, 1-methyl-; Acetic Acid, Butyl Ester
 Minnesota: Benzene, ethyl-; Methanol; 2-Pyrrolidinone, 1-methyl-; Acetic Acid, Butyl Ester
 Massachusetts RTK: Benzene, ethyl-; Methanol; 2-Pyrrolidinone, 1-methyl-; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester
 New Jersey: Benzene, ethyl-; Methanol; 2-Pyrrolidinone, 1-methyl-; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester; Benzene, methyl-
 TSCA 8(b) inventory: Benzene, ethyl-; Benzene, dimethyl-; 1-Butanol; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester; Benzene, methyl-
 TSCA 5(e) substance consent order: Acetic Acid, Butyl Ester
 TSCA 8(d) H and S data reporting: Benzene, ethyl-
 TSCA 12(b) annual export notification: Acetic Acid, Butyl Ester
 SARA 302/304/311/312 hazardous chemicals: Methanol
 CERCLA: Hazardous substances.: Benzene, ethyl-: 1000 lbs. (453.6 kg); Benzene, dimethyl-: 100 lbs. (45.36 kg); Isobutyl alcohol; Methanol; 1-Butanol; 1-Propanol, 2-methyl-; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester; Benzene, methyl-: 1000 lbs. (453.6 kg);

<u>Ingredient name</u>	<u>Cancer</u>	<u>Reproductive</u>	<u>No significant risk level</u>	<u>Maximum acceptable dosage level</u>
2-Pyrrolidinone, 1-methyl-	No.	Yes.	No.	No.
Acetic acid, 2-methylpropyl ester	No.	No.	No.	No.
Quartz (SiO ₂)	Yes.	No.	No.	No.
Carbon Black	Yes.	No.	No.	No.
Benzene, methyl-	No.	Yes.	No.	No.

Canada

WHMIS (Canada) : Class B-2: Flammable liquid
 Class D-1A: Material causing immediate and serious toxic effects (Very toxic).
 Class D-2A: Material causing other toxic effects (Very toxic).
 Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

16. Other information

Label requirements : CANCER HAZARD.
 CONTAINS MATERIAL WHICH CAN CAUSE CANCER.
 CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS:
 BLOOD, KIDNEYS, LUNGS, NERVOUS SYSTEM, LIVER.
 FLAMMABLE LIQUID AND VAPOR.
 VAPOR MAY CAUSE FLASH FIRE.

Hazardous Material Information System (U.S.A) :

Health	*	1
Fire hazard		3
Reactivity		0
		G

16 . Other information

Personal protection

* Indicates may be chronic effects

National Fire Protection Association (U.S.A) :



Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.