Miscellaneous Hinges

107 Degree Opening Hinges CLIP Top Series - 107 Degree Hinges

iblum

Each series features three way independent adjustment. All hinges are metal construction with nickel plated finish.



Self Close

	Straight	Half Crank	Full Crank
	<u>Arm</u>	<u>Arm</u>	<u>Arm</u>
Screw On	BL75T-155	BL75T-165	BL75T-175
Press In	BL75T-158	BL75T-168	BL75T-178
Inserta	BL75T-159	BL75T169	BL75T-179

120 Degree and 120 + Degree Opening Hinges



All metal hinges, nickel plated. Spiral-tech

depth adjustment. Tool free door to cabinet assembly and removal. 3 dimensional independent adjustment. Self closing and free swing versions. INSERTA models provide tool free hinge to door assembly.



CLIP top

120 Degree Series

		Straight	Half Crank
		<u>Arm</u>	<u>Arm</u>
Free Swing	Screw On	BL70T-555	BL70T-565
Č	Press In	BL70T-558	BL70T-568
	Inserta	BL70T-559	BL70T-569
Self Close	Screw On	BL71T-555	BL71T-565
	Press In	BL71T-558	BL71T-568
	Expando	BL71T-558E	N/A
	Inserta	BL71T-559	BL71T-569

*For inset applications, use the half cranked hinge with any 9mm base plate or straight arm hinge with 18mm base plate.

CLIP top

120 + Degree Series

		Straight Arm
Free Swing	Screw On	BL72T-555
C	Press In	BL72T-558
	Inserta	BL72T-559
Self Close	Screw On	BL73T-555
	Press In	BL73T-558
	Inserta	BL73T-559

Blumotion for Doors

No matter how hard you shut the door, when you use BLUMOTION hinge for your doors; it guarantees a smooth, silent close.

BLUMOTION is guaranteed for life installs into end panels or with various adapter plates.



*†blum**

<u>Part #</u>	<u>Description</u>
BL970-1002	Soft close mechanism
BL970-5201	Inline adapter screw on
BL970-5231	Inline adapter press in
BL970-55E1	Expando adapter (37mm set back)
BL970-5701	Face frame adapter – single (9.5mm set
BL970-6701	back) Face frame adapter – double (9.5mm setback)

170 Degree Opening Hinges



Each series features three way independent adjustment. All hinges are metal construction with nickel plated finish and stamped steel cup. Sold per each.



CLIP Series 170 Degree Series Straight (Omm)

LII Series	i / o Degree S	cries Stra
	J	Straight Arm
Self Close	Screw On	BL71T-655
	Press In	BL71T-658
	Inserta	BL71T-654

Half Cranked Arm (9.5mm)

	<u>Half Crank</u>
Self Close	BL71T-665
	BL71T-668
	RI 71T-664

CLIP Top Series

Straight (Omm)

		<u>Full Overlay</u>
Free Swing	Screw On	BL70T-655
C	Press In	BL70T-658
	Inserta	BL70T-654

Half Cranked Arm (9.5mm)

	Half Overlay
Free Swing	BL70T-665
C	BL70T-668

170 Degree Hinge Accessories


Part #	Description
BL80-6107	Hinge Cover Cap
BL80-6507	Steel Cover Cap
BLMZM-0018	170 Degree MINIPRE

BLMZM-0018 170 Degree MINIPRESS Ram BL70-6103 130 Degree Angle Restriction Clip

Notes: For inset applications use the half cranked hinge with any 9mm baseplate.

CLIP Inset Face Frame Adapter Ablum Mounting Plate with Cam BL175H503-21

For use with CLIP and CLIP top half cranked hinges, self closing 100 degree, 107 degree, 120 degree and thick door hinges. Features 9mm height for inset application. Two piece cam height adjustable mounting plate for inset doors. No build up behind face frame is necessary. Can be used on frames with applied bead moulding.



Stamped Steel Face Frame Cam Height Adjustable Adapter Plate

With CLIP top hinges and the new series of cam

height adjustable adapter plates, adjustment in all 3 directions can be made without loosening and retightening fixing screws. For use with CLIP top and CLIP hinges. Available for center mount



?blum°

(9.5mm) and off center (12.5mm) from front edge of face frame. Plate heights available from 0mm to 6mm. Cam height adjustment range of +- 2mm. For wood screw mounting, use #6 x $^{3}4^{\circ}$ wood screws (sold separately).

Part #	Mounting	<u>Height</u>
BL175H6000 BL175H6030	Cam Center Mount	0mm
BL175H6040	Cam Center Mount Cam Center Mount	3mm 4.5mm
BL175H6060 BL175H6600	Cam Center Mount	6mm
BL1/3H0000	Off Center Mount	0mm

Steel Winged Base Plates Stamped Steel Construction

Use with any CLIP, CLIP top or INSERTA

hinge. Pre-mounted Euro Screw base plate can also be fixed with an additional wood screw with wide angle hinges for more stability. Offers height adjustment of +-3mm. Sold per each. Note: for wood screw



iblum

mounting, use #6 x 5/8" wood screws (sold separately).

Part #	Mounting	Height
BL173-810	Pre-Mount Euro Screw	0mm
BL173-813	Pre-Mount Euro Screw	3mm
BL173-610	Wood Screw	0mm

Expando Doweled Base Plates Stamped Steel Construction

iblum

Offers quicker and simpler attachment. Use with any CLIP, CLIP top or INSERTA hinge.
Base plate includes fast, self tapping screws and EXPANDO dowels. Offers a height adjustment of +-2mm. Sold per each.



688-1878

452-2612 688-1993

(800)

Fax

Part #
BL174-710EMounting
Expando DowelHeight
0mm

Zinc Die Cast

Euro Screw Base Plates

Winged base plates featuring pre-mounted Euro Screws. Use of attachment to cabinet with pre-drilled system holes. Use with any CLIP, CLIP top or INSERTA hinge.

Offers height adjustment of +-3mm. Zinc die cast construction, nickel plated finish.

Sold per each.




Ablum

Part #	Mounting	<u>Height</u>
BL175-810	Pre-Mounted Euro Screw	0mm
BL175-813	Pre-Mounted Euro Screw	3mm
BL175-819	Pre-Mounted Euro Screw	9mm

Wood Screw Base Plates Zinc Die Cast Construction

Pblum°

Use for attachment to cabinet with wood screws. Use with any CLIP, CLIP top, or INSERTA hinge. Offers one screw height adjustment of +-2mm. Zinc die cast construction, nickel plated finish. Sold per each, 50 per box. Note: for wood screw mounting,



 Part #
 Mounting
 Height

 BL175-710
 Wood Screws
 0mm

 BL175-713
 Wood Screws
 3mm

 BL175-719
 Wood Screws
 9mm

Miscellaneous Hinges

Variable Mounting Base Plates **Zinc Die Cast Construction**



Winged base plates offer variable mounting options by accommodating wood screws, Euro screws or twin application connecting screws. Use with any CLIP, CLIP top, or INSERTA



hinge. Offers one screw height


adjustment of +-2mm. Zinc die cast construction, nickel plated finish. Sold per each, 50 per box. Note: for wood screw mounting, use #7 x 3/4" wood screws (sold separately).

Part #	Mounting	` 1	Height
BL175-910	Euro Screws		0mm
BL175-913	Euro Screws		3mm
BL175-916	Euro Screws		6mm
BL175-919	Euro Screws		9mm
BL175-919-22	Euro Screws		18mm

Face Frame Adapter Base Plates **Zinc Die Cast Construction**



Designed to allow the use of concealed hinges on face frame cabinets. Accommodates use with any CLIP, CLIP top, or INSERTA hinge. Offers two screw height adjustment of +-2mm. Zinc die cast construction, nickel plated finish. Sold per each. Note:



for wood screw mounting, use #7 x 3/4" wood screws (sold separately)

Part #	Mounting	Height
BL175-660-22	Off Center	0mm
BL175-663-22	Off Center	3mm
BL175-666-22	Off Center	6mm
BL175-603-21**	Center	3mm
**Center mount to th	e face frame	

45 Degree Diagonal **Application Hinges** 110 Degree Opening Cross Corner

Application



Designed specifically for cross corner cabinets. Features three way independent adjustment. Various overlay applications are available. All hinges are metal construction with nickel plated finish. Sold per each.




110° Diagonal Opening

Part #	Cup Mount
BL79T-555	Screw On
BL79T-558	Press In
BL79T-559	Insert

95 Degree Blind Corner Hinges **CLIPtop Series**

Designed specifically for blind corner cabinets. Features three way independent adjustment. Various overlay applications are available. All hinges are metal construction with nickel plated finish. Sold per each.



Blind Corner #	Cup Mount
BL79T-955	Screw On
BL79T-958	Press In
BL79T-959	Inserta

Compact 33

Ablum **Face Frame Hinges**

Various door overlays are achieved by slide on mounting to a variety of base plates. The cup boring pattern matches both the CLIP, CLIP top and INSERTA series. It allows the use of Blum drilling machines. Max drilling distance from edge of door is 3mm. Side adjustment from +0mm to -3mm and height adjustment

of +-3.5mm. All hinges are nickel die cast metal construction. Sold per each.

Part #	Cup Mount
BL33-360-NP	Screw On
BL33-363-NP	Press In

Compact 33

Edge Mounted Base Plate

For mounting, use #6 x 3/4" flat head wood screws, sold separately. Nickel die cast metal construction. Sold per each.

Part #	Inches
BL130-1100-24-NP	1/4"
BL130-1100-23-NP	1/2"
BL130-1100-26-NP	5/8"
BL130-1100-22-NP	3/4"
BL130-111-NP	1"
BL130-112-NP	1 1/8"
BL130-113-NP	1 1/4"
BL130-114-NP	1 3/8"
BL130-115-NP	1 1/2"
BL130-116-NP	1 5/8"



Ablum

Compact 33

Wrap Around Base Plate

iblum

For mounting, use #10 x 3/4" pan head wood screws, sold separately. Nickel die cast metal construction. Sold per each.

Part # BL130-2100-23-NP BL130-2100-26-NP BL130-2100-22-NP BL130-211-NP BL130-212-NP BL130-213-NP BL130-214-NP BL130-215-NP	Inches 1/2 5/8" 3/4" 1" 1 1/8" 1 1/4" 1 3/8" 1 1/2"
BL130-214-NP	1 3/8"
BL130-215-NP	1 1/2"
BL130-216-NP	1 5/8"



iblum

Compact 33

Face Mounted Base Plate

For mounting, use #6 x 3/4" flat head wood screws, sold separately. Nickel die cast metal construction. Sold per each.

Part #	Overlay
BL133-024-NP	1 3/8" +



Compact 38N Overlay Hinges

|blum

105 degree opening angle, 7/16" cup depth, +/1/16" micro side adjustment, +/-1/8" height adjustment, +3/32"
- 1/32" depth adjustment.

Part #	Cup Mount	Overlay
BL38N355-08	Screw On	1/2"
BL38N355-12	Screw On	3/4"
BL38N358-08	Press In	1/2"
BL38N358-10	Press In	5/8"

Connecting "Twin Application"

W

iblum

Flat Head - Slot Drive

Use for mounting Blum CLIP, CLIP top, INSERTA or MODUL base plates on central partitions. Flat head, slotted M4 machine thread. 5mm diameter x 16mm – 20mm length. Sold per each.

(541)

(800)

Fax

688-1878

452-2612 688-1993

Part #	
BL612-2010	Male
BL612-2020	Female 16-20mm
BL 612-2420	Female 20-24mm

3/8" Inset Hinges Modern Design

Use (5) #6 oval head x 5/8" screws. Screws and pads included.





<u>Part #</u>	<u>Color</u>	Box Oty.
AMH7128-A	Almond	sold per pair
AMH7128-3.C	Bright Brass	100 pck
AMH7128-BK	Black	sold per pair
AMH7128-BB.C	Burnished Brass	100 pck
AMH7128-ORB.C	Oil Rubbed Bronze	100 pck
AMH7128-G10.C	Satin Nickel	100 pck
AMH7128-WI	Wrought Iron	sold per pair
AMH7128-W3	White Chrome	sold per pair
AMH7128-W	White	sold per pair
AMH7128-BN	Black Nickel	sold per pair
AMH3428-3	Bright Brass	sold per pair
AMH3428-BB	Burnished Brass	sold per pair
AMH3428-26	Chrome	sold per pair
AMH3428-G10	Satin Nickel	sold per pair
AMH3428-ORB	Oil Rubbed Bronze	sold per pair

Note: In bulk set (100 pck), screws not included.

Miscellaneous Hinges

3/8" Inset Hinges

Edgebrook Manor Design

Solid brass, sold with (5) #5 O.H. x 5/8" screws. Sold per pair.







3/8" Inset Hinges

Carriage House Design

Made of .065 steel. Solid with (5) #5 O.H. x 5/8" screws Sold per pair.


Part #	<u>Color</u>
AMH7328-074	Sterling Brass
AMH7328-AE	Antique English
AMH7328-G9	Antique English Sterling Nickel



3/8" Inset Hinges

Modern Design

Made of .065 steel. Sold with (5) #6 O.H. x 5/8" screws. Sold per pair.





Amerock

3/8" Inset Hinges

Imperia Design

Made of .065 steel. Solid with (5) #5 O.H. x 5/8" screws Sold per pair.

Part #	<u>Color</u>
AMH7928-26	Polished Chrome
AMH7928-3	Bright Brass
AMH7928-3.C	Bright Brass Antique English
AMH7928-AE	Antique English
AMH7928-AE.C	Antique English Burnished Brass
AMH7928-BB	Burnished Brass
AMH7928-G10	Satin Nickel
AMH7928-ORB	Oil Rubbed Bronze

C = 100/box

Amerock



Imperia Design

Variable Overlay

Made of .065 steel Use (2) #5 O.H. x 5/8" and (3) #5 flat head x 1/2" screws. Screws not included. Sold per pair.

Part #	<u>Color</u>
AMH7929-26	Polished Chrome
AMH7929-AE	Antique English Burnished Brass
AMH7929-BB	
AMH7929-3	Bright Brass
AMH7929-G10	Satin Nickel
AMH7929-ORB	Oil Rubbed Bronze





Variable Overlay Hinges

Modern Design

Use (2) #6 O.H. x 5/8" and (3) #6 flat head x 1/2" screws. Screws and pads included. Sold per pair, 25 pairs

<u>Part #</u>	<u>Color</u>
AMH7139-14	Bright Nickel
AMH7139-14.C	Bright Nickel
AMH7139-3.C	Polished Brass
AMH7139-A	Almond
AMH7139-BB.C	Burnished Brass
AMH7139-BN	Black Nickel
AMH7139-CP	Champagne
AMH7139-PWT	Pewter
AMH7139-R3	Rustic Brass
AMH7139-RBZ	Rustic Bronze
AMH7139-W	White
AMH7139-WI	Wrought Iron
AMH7139-ORB.C	Oil Rubbed Bronze
AMH7139-G10.C	Satin Nickel
AMH7139-W3	White w/ Bright Brass
AMH7139-BK	Black
AMH3429-26	Chrome
AMH3429-3	Bright Brass
AMH3429-BB	Burnished Brass
AMH3429-G10	Satin Nickel



Amerock

Variable Overlay Hinges Modern Design

AMH3429-ORB

C = 100 / box

Made of .065 steel Use (2) #5 O.H. x 5/8" and (3) #5 flat head x 1/2" screws. Screws included. Sold per pair.

Part # Color AMH7629-26 Chrome **Burnished Brass** AMH7629-BB



merock

merock

1/2" Overlay Hinge with Vertical Adjustment

Part #

Slotted holes on frame leaf for vertical

adjustment. Use (3) #5 flat head x 1/2" and (2) #6 flat head x 5/8" screws. Sold with screws (no bumper pads). Sold per pair.

Color

Oil Rubbed Bronze

AMH7550-3	Bright Brass
AMH7550-14	Bright Brass Bright Nickel
AMH7550-14.C	Bright Nickel
AMH7550-BB	Burnished Brass
AMH7550-BB.C	Burnished Brass
AMH7550-G10	Satin Nickel
AMH7550-G10.C	Satin Nickel
AMH7550-ORB	Oil Rubbed Bronze
AMH7550-ORB.C	Oil Rubbed Bronze
AMH7550-W	White
AMH7550-WI*	Wrought Iron




*Screws and pads included. Sold per pair, 100 pairs per box. C = 100/box

Amerock

Partial Wrap Finial Hinges

Companion hinges to the True Elegance and Natural Elegance lines of Amerock decorative hardware. Use for 1/2" overlay applications. Self closing action. Use (3) #5 flat head x 1/2" and (2) #6 flat head x 5/8" screws. Screws are included. Bumper pads sold separately. Both sold per pair.



AMH7550T1-077 Brass Tradition

1/2" Overlay Large Tip Finial Color

AMH7550T2-077

Brass Tradition

3/8" Inset Hinge with Finial Tips

Use (5) #5 O.H. x 5/8" screws. Screws included. Sold per pair.

Part #
AMH7687M-14
AMH7687M-AE
AMU7697M DAE

AMH7687M-PB AMH7687M-WI <u>Color</u> Nickel

Antique English Dark Antique English Polished Brass Wrought Iron



(A)merock


Finial Hinges 3/4" Full Wrap Full Set

Non Mortise - Adjustable - Non Self Closing

Same features as the AM3180. Accommodates 3/4" doors. Exclusive pin treatment assures silent, reliable performance. Horizontal/ vertical adjustment. Door gap as small as 1/6". Screws are included. Sold per each.



<u>Color</u> Wrought Iron Oil Rubbed Bronze



Finial Hinges 3/4" Full Inset Ball Tip, Partial Wrap

Part #	<u>C</u>
AMH3180TB-14	Ni
AMH3180TB-AE	Aı
AMH3180TB-DAE	Da
AMH3180TB-FB	Fl
AMH3180TB-G9	St
AMH3180TB-PB	Pc
AMH3180TB-RBZ	Rι
AMH3180TB-SB	Sc
AMH3180TB-WI	W
AMH3180TB-G10	Sa
AMH3180TB-ORB	Oi

AMH3180TB-BB

<u>olor</u> ickel ntique English ark Antique English lat Black terling Nickel olished Brass ustic Bronze

olid Brass rought Iron atin Nickel il Rubbed Bronze **Burnished Brass**



Finial Hinges - Partial Wrap 3/4" Full Inset Minaret Tip

AMH3180TM-14 AMH3180TM-AE AMH3180TM-DAE AMH3180TM-FB AMH3180TM-G9 AMH3180TM-PB AMH3180TM-RBZ AMH3180TM-SB AMH3180TM-WI AMH3180TM-ORB AMH3180TM-G10

AMH3180TM-BB

Nickel

(800)

Fax

Antique English Dark Antique English Flat Black Sterling Nickel Polished Brass Rustic Bronze Solid Brass Wrought Iron Oil Rubbed Bronze Satin Nickel Burnished Brass

688-1878

452-2612 688-1993



merock

Modern Design 30 Degree Reverse Bevel

For reverse bevel doors. Made of .065 steel. Use (5) #5 O.H. x 5/8" screws. Sold per pair.

Color

Part #	
AMH7630-BB	
AMH7630-26	
AMH7630-3	

Burnished Brass Polished Chrome Polished Brass AMH7630-AE Antique English



Amerock

merock

Partial Wrap Hinge Non Self Closing

For 3/4" flush doors. Steel construction. Tight pin. Use (5) #6 flat head x 5/8" screws. Sold with screws. Sold per pair.

Part #	<u>Color</u>
AMH5988-M3	Bright Brass
AMH5988-M26	Chrome



Finial Hinges - Full Wrap Full Inset, Ball Tip

Part # AMH3175TB-AE AMH3175TB-DAE AMH3175TB-G9 AMH3175TB-PB AMH3175TB-WI AMH3175TB-ORB

Antique English Dark Antique English Sterling Nickel Polished Brass Wrought Iron

Oil Rubbed Bronze



merock

merock

Decorative Hinge AMH1622-CB

Surface Mount

For 3/8" inset doors. Weathered steel construction. Screws included. Sold per pair. Available in black.





Miscellaneous Hinges

Double Demountable Wrap Around Hinges




Generous 3 way adjustments, left-right, updown, in-out. Wrap around. Clamps to both frame and door. Self closing action. Steel construction of .065 steel. Mounts to frame with two screws. All

sold per pair. Special order routing machinery required.





<u>1 a1 t π</u>	<u>C0101</u>
AMH8700-3	Bright Brass
AMH8700-3.C	Bright Brass
AMH8700-BB	Burnished Brass
AMH8700-BB.C	Burnished Brass
AMH8700-G9.C	Sterling Nickel
AMH8700-G10	Satin Nickel
AMH8700-G10.C	Satin Nickel
AMH8700-ORB	Oil Rubbed Bronze
AMH8700-ORB.C	Oil Rubbed Bronze
=100 pr count (speci	al order, full box only)





Bright Brass Burnished Brass Burnished Brass Sterling Nickel Satin Nickel Satin Nickel AMH8701-BB.C AMH8701-G9.C AMH8701-G10 AMH8701-G10.C AMH8701-ORB Oil Rubbed Bronze AMH8701-ORB.C Oil Rubbed Bronze C=100 pr count (special order, full box only)

1/2" Overlay Hinges

•	0
Part #	<u>Color</u>
AMH8704-3	Bright Brass Bright Brass
AMH8704-3.C	Bright Brass
AMH8704-AE	Antique English Burnished Brass
AMH8704-BB	Burnished Brass
AMH8704-BB.C	Burnished Brass
AMH8704-G9	Sterling Nickel
AMH8704-G9.C	Sterling Nickel
AMH8704-G10	Satin Nickel
AMH8704-G10.C	Satin Nickel
AMH8704-ORB	Oil Rubbed Bronze
AMH8704-ORB.C	Oil Rubbed Bronze
C=100 pr count (spec	ial order, full box only)

Special Demountable Hinge Bits



Use for cutting openings for demountable hinges. Two flutes.

Part #	Description	Diameter	Shank Dia.
AT48100	F/ Door	1 1/8" 1 1/8"	3/8" 1/2"
AT48101 AT48102	F/ Door F/ Face Frame	1 1/8"	$\frac{1}{2}$ "

Single Demountable Hinges Partial Wrap



Self closing action. Steel construction of .065

3/8" Inset Hinge

3/8" overlay with 3/8" inset. Use (2) #6 flat head x 5/8" screws. Fully adjustable frame wing. Sold per pair.

<u>Part #</u>	<u>Color</u>
AMH8714-BB	Burnished Brass
AMH8714-BB.C	Burnished Brass
AMH8714-3	Polished Brass
AMH8714-3.C	Polished Brass
AMH8714-G10	Satin Nickel
AMH8714-G10.C	Satin Nickel
AMH8714-ORB	Oil Rubbed Bronze
AMH8714-ORB.C	Oil Rubbed Bronze
C=100 pr count (speci	ial order, full box only)

Overlay Hinge

Features fully adjustable frame wing. Uses (2) #6 flat head x 5/8" screws. Sold per pair.

<u>Part #</u>	<u>Color</u>
AMH8715-BB	Burnished Brass
AMH8715-3	Polished Brass
AMH8715-3.C	Polished Brass
AMH8715-G10	Satin Nickel
AMH8715-G10.C	Satin Nickel
AMH8715-ORB	Oil Rubbed Bronze
AMH8715-ORB.C	Oil Rubbed Bronze
C-100 pr count (cnoc	ial order full how only)

C=100 pr count (special order, full box only)

1/2" Overlay Hinge

Part #	Color	8
AMH8719-3	Bright Brass	
AMH8719-3.C	Bright Brass	П
AMH8719-BB	Burnished Brass	1
AMH8719-BB.C	Burnished Brass	1
AMH8719-G10	Satin Nickel	
AMH8719-G10.C	Satin Nickel	
AMH8719-ORB	Oil Rubbed Bronze	u
AMH8719-ORB.C	Oil Rubbed Bronze	
AMH8719-14.C	Nickel	
1 100	1 1 0 111 1 1	

C=100 pr count (special order, full box only)


30 Degree Reverse Bevel Hinge

9/32" inset. Fully adjustable frame wing. Use (2) #6 flat head x 5/8" screws. Sold per pair.

Part # Co	<u>olor</u>
AMH8724-BB Bu	urnished Brass

Cedar Chest Hinge

Heavy gauge scissor action hinge. Specially designed to lift overlay lids on cedar chests, hampers, hassocks, tool chests or radiator covers. Also serves to control drop down action on cabinet fronts. Steel construction.





Part #	<u>Color</u>
SYH2300	Brass

Gravity Pivot Hinge Cafe Style Door



Designed for quiet, carefree operation

of louver or dwarf doors (or low use, light weight café doors) from 3/4" to 1 3/8" thick. Offers an adjustment feature to align doors. Holds door open at 90 degrees and also returns door to center of opening automatically. Door weight carried on tough, silent nylon bearings. Steel construction. Satin brass plated finish. Screws included. Sold per pair.

Part# Color STH150-US4 Satin Brass Plated










Gate Type Spring Pivot Hinges 75 lb Capacity

(800)

Fax

Double acting. Non-handed. Surface pivot with adjustable tension. Flat type jamb brackets 1 1/4" wide. Flat gate brackets for doors minimum 1" thick. Screws (10) #12 x 1 1/4" flat head wood screws. 36" maximum width, 2 1/2" maximum thickness, 76 lbs maximum weight. Steel construction. Set includes hinges (top and bottom), door brackets, jamb brackets and screws. Sold per set.





Bommer

688-1878

452-2612 688-1993

Gravity Pivot Hinge

Bommer Double action hinges. Non-handed. Gravity close. 30" maximum door width, 50 lbs maximum capacity. Flat type brackets for door 7/8" to 1 5/8" thick. Flat type jamb brackets 1 1/4" wide. Use (4) #10 x 1" flat head wood screws, included. Steel construction. Sets include hinges (top and bottom), door brackets, jamb brackets and screws. Sold per set, 1 per box

Part #	Description	<u>Color</u>
BM7512H-633	90 degree hold open	Dull Brass
BM7512-633	Non hold open	Dull Brass
BM7512H-603	90 degree hold open	Zinc
BM7512-603	Non hold open	Zinc

Heavy Duty Table Flap Hinge

Extra heavy duty 13 gauge steel. Quickly converts square table tops to round tops, adds length to oblong tops, increases seating capacity in a matter of seconds. 30" square table opens to 42" round. 36" square table opens to 51" round. 42" square table opens to 60" round table. Spring steel clips hold flaps securely under table top when not in use. Flaps open 180 degree and automatically lock into the open, level position when needed. Brass plated, with friction catch and 4 heavy duty steel springs. Screws included (48 specially threaded). 8 hinges per set, sold per set.

Color Part # FT22203 Brass

Pivot Hinge/ Pin Hinge Overlay

23/32" overlay for door 3/4" thick. Steel construction .083" thick. Use (6) #6 flat head x 5/8" screws.

<u>Part #</u>	<u>Color</u>
AMH1238-2G	Perma Brit Zinc
AMH1238-BB	Burnished Brass

Variable Overlay

For doors 3/4" thick. Steel construction .083" thick. Use (6) #6 flat head x 5/8" screws. Right and left handed pairs. Screws included. Sold per pair.

Part #	Color
AMH1242-2G	Perma Brit Zinc
AMH1242-BB	Burnished Brass




merock



Miscellaneous Hinges

Slant Top Hinge and Support

Acts as both a hinge and a support. Designed for desks with fold down tops that close on a slant (30 degree or more). Free acting no catch or



lock. The ratchet type joint is fully enclosed when the top is folded down. Hinge support non-handed. 7" open length x 4 3/4" closed length x 3/4" wide. Steel construction with antique brass finish. Use #8 x 5/8" screws, sold separately. Sold per each.

Part#

YYSTH-AB **Antique Brass**

Finial Butt Hinges

Size 1 1/2" x 1 1/2". Uses (4) #4 x 1/2" flat head screws. Screws included. Steel is .037 gauge construction. Sold per pair.

Part#

Antique English AMH2335-AE

Size 2" x 1 3/8". Uses (6) #5 x 5/8" flat head screws. Screws included. Steel is .042 gauge construction. Sold per pair.



Part # Color

AMH2355-AE Antique English



merock

Non-Mortise Finial Hinge 2" Hinge

2" long x 3/4" leaf width. Uses #4 x 1/2" screws. Screws sold separately. Sold per each.




Antique Brass SY266-2AB

2 1/2" Hinge

2 1/2" long x 7/8" leaf width. Uses #5 x 1/2" screws. Screws sold separately. Sold per each, 100 per box.

Part # Color SY266-2.5AB Antique Brass




Non-Mortise Butt Hinge

For cabinets and furniture. Precision made, heavy gauge for hanging heavy doors without any mortising or other fittings. 2" long x 15/16" leaf width. Tight hinge pin. Use #4 x 12" screws, sold separately. Heavy gauge steel construction. Sold per each.

Part #	Color	Dimensions
SYH266-2LAQP	Brass	2" x 15/16"
SYH266-2N	Nickel	2" x 15/16"
SYH266-112LAQP	Brass	1.5" x 13/16"





Heavy Duty Double Action Spring Hinge

Allows door to open in either direction. Automatically returns to closed position. Does not offer hold open action. Non-handed. Resiliency of spring support and shock absorbing reaction of flexible mounting provides maximum protection. Adjustable closing spring tension. Door flange must be mortised in door. Jamb flange surface applied to face of frame. No hanging strip required. Steel construction. Screws included. Sold per pair, 1 pair per box. It is advisable to use three



hinges per door. The center hinge should be installed as close as possible to the top hinge for maximum support. Hinge capacity decreases as door height increases.

35/38" lb Capacity

With two hinges per door, maximum door width is 24" and 35 lbs. capacity. With three hinges per door, maximum door width is 32" width with 38 lbs. capacity. Designed for doors from 3/4" to 1" thick. Maximum height is 5' tall.

Part #	Color
BM3029-3-632	Brass
BM3029-3-603 BM3029-3-633	Zinc Satin Brass

60/75" lb Capacity

With two hinges per door, maximum door width is 28" and 60 lbs. capacity. With three hinges per door, maximum door width is 36" width with 75 lbs. capacity. Designed for doors from 7/8" to 1 1/4" thick. Maximum height is 6'8" tall.

Part #	<u>Color</u>
BM3029-4-632	Brass
BM3029-4-603	Zinc
BM3029-4-633	Satin Brass


75/107" lb Capacity

With two hinges per door, maximum door width is 32" and 75 lbs. capacity. With three hinges per door, maximum door width is 36" width with 107 lbs. capacity. Designed for doors from 1 1/4" to 1 3/4" thick. Maximum height is 7" tall.


Color Part # BM3029-6-632 Brass BM3029-6-603

Bommer

Double Acting Spring Hinges (Light) Duty)



fits louver doors 1 1/8" to 1 1/2" thick







1515 Shown

(541)688-1878 (800)452-2612 Fax

688-1993

Miscellaneous Hinges

Knife Hinges

Concealed Self Latching

Youngdale

Improves quality. Reduces assembly time. Insures perfect alignment. Lifetime guaranteed spring and roller closing assembly. High production standards. Constructed of the best materials available. No recall due to faulty hinges. Exceeds cabinet association requirements. Locating tabs on door and stile. Plans for notching jig available. Fully adjustable.

Easy to install. Requires minimum 9/32" saw kerf. Metal construction. Sold per pair.


1/4" Overlay

Part #	<u>Color</u>	Otv.
YD3-AB-100	Antique Brass	100 pck
YD3-AB-POLY	Antique Brass	Poly-bagged
YB3-NI-100 YB3-NI-POLY	Nickel Nickel	100 pck Poly-bagged
		Poly-bagged
YD3-WH-100	White	100 pck Poly-bagged
YD3-WH-POLY	White	Poly-bagged



Includes pads and screws.

mercial paras ama	010 (10)	
Part #	<u>Color</u>	Otv.
YD4-3-100	Brass	100 pck
YD4-3-POLY	Brass	Poly-bagged
YD4-AB-100	Antique Brass	100 pck
YD4-AB-POLY	Antique Brass	Poly-bagged
YD4-NI-100	Nickel	100 pck
YD4-NI-POLY	Nickel	Poly-bagged
YD4-WH-100	White	100 pck
YD4-WH-POLY	White	Poly-bagged



1/4" Overlay Thick Door

Includes pads and screws.

Part #	<u>Color</u>	Otv.
YD5-WH-100	White	100 pck
YD5-WH-POLY	White	Poly-bagged
YD5-AB-100	Antique Brass	100 pck
YD5-AB-POLY	Antique Brass Antique Brass	100 pck Poly-bagged

1/2" Overlay Thick Door

Includes pads and screws.

Part #	<u>Color</u>	Otv.
YD6-3-100	Brass	100 pck
YD6-3-POLY	Brass	Poly-bagged
YD6-AB-100	Antique Brass Antique Brass	100 pck
YD6-AB-POLY	Antique Brass	Poly-bagged
YD6-NI-100	Nickel	100 pck
YD6-NI-POLY	Nickel	Poly-bagged
YD6-WH-100	White	100 pck
YD6-WH-POLY	White	Poly-bagged

1/2" Overlay

127 degree opening

Part # Colo	
	que Brass Poly-bagged que Brass 100 pck

Plain Edge Door Application

1 1/2" Face Frame	1"Thick Door
1" Shadow Line	155 degree Opening

Miscellaneous Hinges

90 Degree Opening Top Lid Hinge

Flush opening lift lid hinge for hampers, chest lids, piano benches, etc. Spring closing, surface mounted, no hole boring or pre-mounting plates. 5 3/4"

long x 13/16" wide. Steel construction, nickel plated. Sold per each.

Part #	<u>Color</u>
SYH2000/90Z	Nickel

Special order item.



6' Piano Hinge

Counter sink screw holes on 2" centers. Requires 72 screws for each 6' length. 3/16" (5mm) knuckle diameter. Screws sold separately. 1mm thick metal construction. Sold in 6' lengths only. Sold per each.



Part #	Open Width	<u>Gauge</u>	<u>Finish</u>
PA116B	1 1/6"	.040	Brass Plated Steel
PA116N	1 1/6"	.040	Nickel Plated Steel
PA114B	1 1/4"	.040	Brass Plated Steel
PA114N	1 1/4"	.040	Nickel Plated Steel
PA112B	1 1/2"	.040	Brass Plated Steel
PA112N	1 1/2"	.040	Nickel Plated Steel
PA2B	2"	.045	Brass Plated Steel
PA2N	2"	.045	Nickel Plated Steel

J.G. Edelen ED6014



To find inch-pounds, multiply one half the distance from front to back times the weight of the lid.

Spring Color	Low Limit	High Limit
White*	110	140
Orange*	95	125
Yellow	65	95
Black*	55	65
Maroon*	45	55
Green*	40	45
Blue*	35	40
Grey*	20	35
* Special Order		

J.G. Edelen ED3038-34

3/4" Double Acting Hinge, brass plated, statuary bronze for 3/4", 7/8", 1 1/8" and 1 1/4" thickness of wood.



Hardware Resources
HW20251PB 3 1/2" Leaf Flag
Hinge for 1" 1 1/18" Panels







Bumper Specialties

- Molded, Self-Adhesive, 100% Polyurethane Bumpers
- Stocked in Clear only
- Custom shapes, sizes, colors and pad configurations are available for special order
- Clear bumpers are practically invisible when applied to colored or see through surface
- All bumpers available in aggressive synthetic rubber adhesive or high performance Acrylic Adhesive

Ideas for use

- Holds cutting boards firmly in place on counter surface
- Keeps picture frames stable, preventing from damaging walls
- Dampens harsh sounds of slamming cabinet doors, drawers or lids
- Prevents speakers, electronics and computers form vibrating or sliding
- Quiet door knobs, eliminating nicks and unsightly damage to walls





BS12SD

BS33SD

<u> Part #</u>	
BS12SD	
BS1SD	
BS33SD	
BS58SD	
BS7	

Description Dome Dumpers Flat Bumper Pyramid Shape Cone Shape Simple

Dimensions

.375 diam x .15 ht diam x .14 ht 5 diam x .15 ht 5 diam x .20 ht 335 diam x .085 ht



BS01SD



(541)

(800)

Fax

688-1878

452-2612 688-1993

BS58SD




BS7

Door Bumper Pads


Features

- 3/8" diameter x 3/32" thick
- White pads are 1/8" thick

Part #	Description	Size per roll
DF38FBR-1M	Brown Felt	1,000
DF38FBR-5M	Brown Felt	5,000
DF38FWH-1M	White Felt	1,000
DFH38N-1M	Hex Natural Rubber	1,000
DFH38N-5M	Hex Natural Rubber	5,000
DFR38N-1M	Round Natural Rubber	1,000
DFR38N-5M	Round Natural Rubber	5,000



DF38FBR



DFH38N



Miscellaneous Hinges

U.S. Futaba

Concealed Hinges (2000 Series)

90° Door Opening

Features

- · Requires no boring
- One hinge accommodates various overlays
 - Self closing
- Door thickness up to 20mm

Part # Description FT2000 90° door opening



U.S. Futaba

Concealed Hinges (2000 Series)

150° Door Opening

Features

- Requires no boring
- One hinge accommodates various overlays
- Self closing
- Door thickness up to 20mm

Part # Description 150° door opening

U.S. Futaba, Inc.

U.S. Futaba, Inc.



U.S. Futaba

Concealed Hinges (2000 Series)

170° Door Opening

Features

- Requires no boring
- One hinge accommodates various overlays
- Self closing
- Door thickness up to 20mm

Part # Description
FT2000/170 170° door opening

U.S. Futaba, Inc.



U.S. Futaba

Bi-Fold Hinge

Features

- · Perfect for entertainment centers with folding doors
- Built in stop
- Spring action (various tensions)
- Material made of zamak
- Available in black

Part # FT21050-000-00 Size 2 3/8" x 2 9/16" • 60.5 x 65mm

U.S. Futaba, Inc.



Fax

Miscellaneous Hinges

Invisible Cylinder Hinges

Designed for completely concealed hinge applications. Opens to 180 degrees. Drill holes using exact bit diameter of hinge, do not use oversize bits to drill holes. To install, tap hinge into hole until flush. Then tightening the set screw expands the specially designed wedge for permanent fastening. The wedge expands and is pressed against the side of the hole for a tight, permanent fit. Steel construction linkage. Solid brass construction, matte brass finish. Sold per each, box quantities noted.

Part #	Diameter	Wood Thickness
FT20571	10mm	1/2"
FT20572	12mm	5/8"
FT20573	14mm	3/4"
FT20574	16mm	7/8"
FT20575	18mm	1 1/8"
FT20576	24mm	1 1/4"



SOSS SOSS Invisible Hinges **Invisible Hinges**

Can be used for computers, cash registers, copy machines, medical equipment and cases, scales and office equipment. They are used in corporate jets, custom furniture and custom casework cabinetry.

They open a full 180°. Ideally suited for mirrored or appliquéd doors and panels, pass doors, electronic cabinets. The moving pivot point remains inside the hinge during travel until fully opened, eliminating an external pinch point on the backside of the

ı	u001.					
ı	Part #	Wood Thickness			Sass	3283
ı	SOS100US4	1/2" (12.70mm)		\$165.000 \$150.000	3	
ı	SOS101US4	1/2" (12.70mm)		\$50.85E		
ı	SOS103US4	3/4" (19.05mm)				
ı	SOS203US4	3/4" (19.05mm)		1 2505t		
ı	SOS204US4	3/4" (19.05mm)		The state of the s	25074	Feero
ı	SOS208US4	1" (25.40mm)	HON HON	0	6 6	00
ı	SOS216US4	1 3/8" (34.93mm)		0		
l	SOS218US4	1 3/4" (44.45mm)	SOSTOOLISA	0000001104		
1			<u>803100034</u>	SUS203US4	SOS204US4	SOS218US4

Glass Door Hinge (510)

Features

- Shallow channel glass door hinge for 1/4" and 3/16" glass
- Poly bagged with two hinges, two plastic bushings, two metal plates and screws
- Plastic bushings press-fit into 8.5 hole
- The 5mm pin on the hinge fits into the plastic bushing

Part #	Color/Finish
EP510BK	Black
EP510B	Polished Brass
FP510CR	Polished Chrome





U.S. Futaba Lift Flap Hinge

Features

- With spring
- Lift and right hand
- 75° opening
- Key hole mounting for doors
- Made from hardened steel
- Available in white epoxy

<u>Part #</u> FT22360-WH <u>Description</u> White lift flap hinge

U.S. Futaba, Inc.



Miscellaneous Hinges

Rockford Industries

Overlay Hinges

Offers a wide selection of 5-knuckle overlay hinges, 2 3/4" in height to meet the requirements of your application.

All hinges have as standard hospital tips 270° opening angle; drilled knuckle IDs and machined knuckle edges for smooth operation; and a non-removable knurled pin.



The 370 Series overlay hinges met ANSI/BHMA 156.9 Grade 1 requirements. The 370 Series overlay hinges are designed for the 32mm side panel line boring system. All mounting holes are countersunk for #8 flat head screws.

	Side	Door	Hinge	Door		Material		
<u>Part#</u> RP374-26D	<u>Panel</u> 3/4"	Thickness 3/4"	<u>Overlay</u> 23/32"	<u>Overlay</u> 15/32"	<u>Reveal</u> 9/32"	Thickness .095	<u>Color</u>	Comments 32mm System,
RP374-BK	(19mm) 3/4"	(19mm) 3/4"	(18.3mm) 23/32"	(11.9mm) 15/32"	(7.1mm) 9/32"	(2.4mm) .095	Chrome	Side Panel 32mm System,
RP376-BK	(19mm) 3/4"	(19mm) 13/16"	(18.3mm) 23/32"	(11.9mm) 15/32"	(7.1mm) 9/32"	(2.4mm) .095	Black	Side Panel 32mm System,
	(19mm)	(20.6 mm)	(18.3mm)	(11.9mm)	(7.1 mm)	(2.4mm)	Black	Side Panel

Rockford Industries

Flush Hinges

Flush hinges are hospital tipped and available in knuckle heights of 2", 2 1/2" and 2 3/4".

	Side	Door	Door	Cabinet	Barrel_	Material
<u>Part#</u>	Panel	Thickness	Clearance	Wing length	<u>Height</u>	Thickness
RP860-26D		3/4"	7/32"	1 59/64"	2 1/2"	.083
		(19mm)	(5.6mm)	(48.8mm)	(63.5 mm)	(2.1 mm)



Selby Hinges

Butler Tray Hinges SYH3640RDP


Features

- Solid brass, round ends, satin finish
- 3" long x 1 1/2" wide
- Authentic reproduction English Butler Tray Hinges
- Locks open in flat position
- Holds vertical at 90°

No Mortise Lid Hinges SYH370/34

Features


- Lift lids for stereos, toy chests, piano benches and headboard comparments
- Steel, brass or bronze finish
- Opens 195°





688-1878

452-2612 688-1993



(800)


Fax



Multi Purpose Reversing Hinges

SYH98-B Brass SYH98N Nickel

A unique loose pin hinge that changes from a flush inset door hinge to an overlay door hinge by removing the pin and reversing the small leaf. Inset door opens 180° and overlay door opens 270°. .054 steel in brilliant nickel or brass.



Light Narrow Butts Hinge

Features

- Fast pin, non-swaged, steel
- · Brass, stat. bronze or nickel plated

<u>Part #</u> SYH931-112P SYH931-2P	Length 1 1/2" 2"	Width Open 1 1/2" 1 3/8"	Steel Gauge .035 .040	No of Holes 4 6	Finish Brass Plated Brass Plated
-------------------------------------------	------------------	--------------------------------	------------------------------	-----------------------	----------------------------------------





Selby Hinges

Flip Top Table Hinges SYH116P

Features

- Solid brass, opens 180°, closes flush
- Polished brass
- 2 3/4" long x 1 3/16" wide





Drop Leaf Hinges SYH278-L

Features

- 3" long x 1 1/4" wide
- Back flap hinge, countersunk on flat side
- Unequal leaf, steel, stat. bronze finish



Features

- 3 1.4: long x 1 3/16" wide
- Flap hinge and sewing machine hinge
- Stat. bronze or brass plated



