Laminate Supplies

Maverick Hardware

Wilsonart Supplies

ColorFlex

Custom colored acrylic latex caulk with silicone. ColorFlex is designed for corner and perimeter caulking of decorative surfaces. After the component (counter, vanity, bath surround, etc.) is installed and the laminate seams have been filled with SeamFil, ColorFlex is used to seal the inside corners and perimeter of the component. Where



flexibility is needed, ColorFlex is perfect for filling gaps and sealing places where components meet the walls, floors, cabinets, tile or insets.

ColorFlex II

Custom colored high-gloss acrylic caulk. Like ColorFlex, ColorFlex II is used for corner and perimeter caulking of decorative surfaces. ColorFlex II, however, has adhesive qualities tht bonds components together unlike its successor. Typical applications for this product are sealing miter joints, setting backsplashes on counter decks and caulking vertical and horizontal corners. *40 plus colors available.*




SeamFil Retarder

SeamFil is formulated to dry quickly, so that the countertop can be put into service immediately after touch up. In a few instances, such as when you are matching a particularly tricky color, you need a longer drying time. A few drops of the retarder in the mix will allow enough time to get a perfect match.



SeamFil Solid Kit

Repairs nicks seams and gouges with ease. Bonds mechanically to substrate of surface. Dries hard and becomes a permanent part of the laminate surface. Resists moisture, detergents and other household products as effectively as the original laminate. Also works well on cracks, chips and other imperfections where the dark substrate is visible.







SeamFil Solvent

Solvent for use in preparing joint and cleaning up excess SeamFil. Excellent for cleaning up contact cement, removing print from laminate and cleaning up spray and rolling equipment.





(541) 688-1878 (800) 452-2612

Fax 688-1993

Wilsonart Supplies

SeamFil Standard Colors

Repairs nicks seams and gouges with ease. Bonds mechanically to substrate of surface. Dries hard and becomes a permanent part of the laminate surface. Resists moisture, detergents and other household products as effectively as the original laminate. Also works well on cracks, chips and other imperfections where the dark substrate is visible.

Available in 21 different colors. Each tube is 1 ounce. Refer to SeamFil color matching guide to determine mixing proportions.





SeamFil Woodgrain Kit

Repairs nicks seams and gouges with ease. Bonds mechanically to substrate of surface. Dries hard and becomes a permanent part of the laminate surface. Resists moisture, detergents

and other household products as effectively as the original laminate. Also works well on cracks, chips and other imperfections where the dark substrate is visible.

Kit contains -1 ounce of the 12 most popular colors to match wood grains surfaces, non scratch putty knife and ½ pint of solvent and complete instructions.





Maverick Hardware

Adhesives

Wilsonart 500

Extremely Flammable Roller Grade Contact Adhesive

Our most popular roller and brush grade contact adhesive. Fast drying, high solids and easy roller application for professional use only.





Wilsonart 800/801

Extremely Flammable Premium Spray Grade Contact Adhesive

The original high speed industry standard spray applied contact adhesive especially formulated for post forming applications. Versatile, in all types of weather, fast drying, easy application by hand or automatic equipment. Never needs stirring. An application and a bond that will last a lifetime.






Permagrip 107

Hi Temp Aerosol Adhesive

A high temperature resistant, high performance grade contact adhesive in a flammable propellant. Very high strength adhesive formulated for the woodworking and marine industries. Its shear and peel strength makes it ideal for bonding high pressure laminates to various substrates and auto, RV and boat interiors. Fast dry times of 1 to 2 minutes and 5 to 10 minutes open time make this a very production efficient product. Times may vary due to temperature and humidity. Free of ozone depleting chemicals and free of CFC's. Self contained system affords portability not allowed by more traditional spray systems. Approximately 64 sq ft per pound coverage.







(541) 688-1878 (800) 452-2612 Fax 688-1993

Shears

Cutters and Shears for Plastic Laminate GU11-LS Regular Plastic Laminate Shears

Capable of making straight cuts on all types of decorative plastic laminate, the patented, 'double action', hardened steel cutting blades of this tool cut without binding, and will not crack or chip the decorative surface. Widely used by professional and do it yourself installers for rough cutting laminate before cementing in place. Can also be used to cut the irregular contour line for the laminate piece that fits between a wall and the backsplash top. Has vinyl coated handles for comfort, and the spring return handles can be locked in the closed position. Tool has a 1 7/16" length of cut with a 9/64" kerf.



Cutters and Shears for Plastic Laminate

GU10-LS Plastic Laminate Shears

This old style shear cuts clean un-chipped edges like the GU11-LS shears. But the handles are held under the sheet when in use, rather than over. This permits cutting across a piece of coved laminate. Has vinyl coated handles for comfort and the spring return handles can be locked in the closed position. Tool has a 1 1/8" length of cut with 9/64" kerf.



Gundlach

GU344 Plastic Laminate Scoring Cutter

Featuring a double edged blade, this a very popular, inexpensive and easy to use tool. The carbide tipped blade simply cores through the decorative surface, and the laminate breaks cleaning away. Ideal for both do it yourself and professional installers. Excellent for cutting self edging strips. Double edged blades are more economical.



Gundlach

GU344-B Scoring Replacement Knife Blade Replacement blade for GU344.






Maverick Hardware

Rollers

Extension Handle Roller

GU333-AR Extension Handle Roller





Seam and Tile Rollers

GU4-L 9" Long Seam and Tile Rollers

Widely used for sheet vinyl seam work, 'rolling in' resilient tile hot cuts and for floor and counter top covering work. The machined and polished steel rollers are 2" wide x 2" diameter, and are mounted on a smooth rolling ball bearing. The wood handles are shaped for a comfortable grip and are securely fastened to the bracket.



Bent Handle Pressure Roller TNPR3

Features

- · Heavy duty roller
- 3" x 1/12" (75 x 38 Ø mm)
- Black rubber roller
- 2 heavy duty ribbed grips
- Zinc plated steel handle

"J" Pressure Roller TNJR3

Features

- For exerting pressure on plastic laminates and veneers
- 3" x 1/12" (75 x 38 Ø mm)
- Black rubber roller
- 2 heavy duty ribbed grips
- No axel projection

Double Edge Squeeze Roller TNSQZR

Features

- Lever action pressures edge of laminate to substrate
- Excellent for correcting edge lifts
- Aluminum handle
- Two polypropylene white rollers
- Vinyl grip

Trim Ease Stick TNTM2

Features

- Prevents bearing pilot burns on laminate
- 24 per box
- 4" x ½"











(541) 688-1878 (800) 452-2612 Fax 688-1993

Laminate Supplies

Simonds

SI10B 10" All Purpose Black Maxi Sharp Files

All purpose, the built in handle provides maximum versatility for a wide range of applications. All purpose files feature a double cut on one side and a single cut on the other side, have one edge cut and one edge safe (uncut) for shoulder filing and are parallel in width and thickness.





Simonds

SI10BMK 10" Multi-Kut Flat

Obtain almost any required finish simply by changing the feed pressure. Multi-Kut Flat Files are single-cut coarse tooth files that taper toward the point in width. Simonds exclusive Multi-Kut design features a diamond pattern "double chip-breaker" allowing for fast stok removal while



leaving a smooth finish. So versatile, the Simonds Multi-Kut combines the performances of Flat and Mill Files.

Simonds

SIFC File Card with Brush

Used to clean files – files last longer when kept properly cleaned. Excess build up can cause clogging resulting in slipping, scratching, or other filing specifications.



