1. Product and Company Identification

Product Name:**2P-10 Thick Cyanoacrylate Adhesive**Part Number:**2P-10 SOLO THICK 2 OZ / 2P-10 THICK 10 OZ**Revision Date:October 9, 2009Company Name:FastCap LLC3725 Irongate Rd.Bellingham, WA 98226

EMERGENCY PHONE: For Chemical Emergency Spill Leak Fire Exposure or Accident only Call CHEMTREC Day or Night

DOMESTIC NORTH AMERICA 800-424-9300 INTERNATIONAL, CALL +1 703-527-3887 (collect calls accepted)

For all other questions or technical issues call, 888-443-3748

2. Composition, Information and Ingredients

Ingredients	CAS NO.	%
Ethyl Cyanoacrylate ester HYDROQUINONE	Proprietary 123-31-9	90-95 0.1-1
Ingredients, which have exp	posure limits	
Exposure Limits: Ingredients	(TWA) ACGIH OSHA (TLV) (PEL)	OTHER
Ethyl Cyanoacrylate HYDROQUINONE	None None 2mg/m3 TWA 2 mg/m3 TW	0.2 ppm TWA A 2 mg/m3 TWA 4 mg/m3 STEL
3. Hazards Identification		
	kin contact may cause burns, Bonds ski kin and eye irritant	n rapidly and strongly
Primary Routes of Entry: No Signs and Symptoms Of Exposure:	one Known Vapor is irritating to eyes and muco Exposure to vapors above the esta Symptoms of non-allergic asthma.	
Existing Conditions Aggravated by Exposure: None Known		
	Literature Referenced Farget organ and other Health Effects	Carcinogen NTP IARC OSHA
Cyanoacrylate ester Poly (methyl methacrylate) Cyanoacetate	ALG IRR IRR NTO	NO NO NO NO N/A NO NO NO NO

HYDROQUINONE BLO BNM CNS IMM IRR LIV MUT NO N/A NO SKI THY

Abbreviations

N/A Not ApplicableALG AllergenBLO BloodBNM Bone MarrowCNS Central nervous systemEYE eyesIMM Immune SystemIRR IrritantLIV LiverMUT MutagenNTO No Target OrgansSKI SkinTHY ThyroidSKI Skin

4. First Aid Measures

Ingestion:Ingestion is not likely. See supplemental page for emergency proceduresInhalation:Remove to fresh air. If symptoms persist, obtain medical attention.Skin Contact:Soak in warm water. See supplemental page for emergency procedures.Eye Contact:Flush with water. See supplemental page for emergency procedures.

5. Flammability and Explosive Properties

Flash Point:	160 -200 [°] F	Method: Tag Closed Cup
Estimated NFPA Code:	2	
Health Hazard: Fire Hazard:	2 2	
Reactivity Hazard:	2	
Specific Hazard:	No Water	
Estimated HMIS Code:		
Health Hazard:	2	
Flammability Hazard:	2	
Reactivity Hazard:	2	
Personal Protection:	See Section 8	5
Recommended		
Extinguishing Agents:	Carbon dioxid	e, foam, dry chemical
Special Firefighting		
Procedures:	Not Available	
Hazardous Products Formed		
By fire or thermal, decomp	Irritating Orga None	nic vapors
Unusual fire or explosion Hazards	NULLE	
Explosive Limits:		
(% by volume in air) Lower	Not Available	
(% by volume in air) Upper	Not Available	

6. Accidental Release Measures

Steps to be taken in case of spill or leak: Flood with water to polymerize. Soak up with an inert absorbent.

7. Handling Controls, Personal Protection

Safe Storage: Store below 75° F Heading: Avoid skin or eye contact. Avoid breathing vapor.

8. Exposure Controls, Persoan Protection

Eyes:	Safety glasses or goggles
Skin:	Nitrile or polyethylene gloves and aprons
	Do not use cotton
Ventilation:	Local ventilation may be desirable when using large amounts in a confined area.

Respiratory: Not Available

See section 2 for Exposure Limits

9. Physical and Chemical Properties

Appearance:	Clear colored liquid
Odor:	Negligible
Boiling Point:	More than 300° F
Ph:	Does not apply
Solubility in Water:	Polymerized by water
Specific Gravity:	1.1

10. Stability and Reactivity

Stability:	Stable
Hazardous Polymerization:	Will not occur
Incompatibility:	Polymerized by contacts water, alcohols, amines or alkalis
Conditions to avoid:	Not Available
Hazardous Decomposition	
Products (non-thermal):	None

11. Toxicological Information:

Estimated oral LD50 more than 5000 mg/kg Estimated dermal LD50 more than 2000 mg/kg

12. Ecological Information

No Data Available

13. Disposal Considerations

Recommended methods of	
Disposal:	Polymerize as above. Incinerate following EPA and local regulations.
EPA Hazardous waste	
Number:	NH- Not a RCRA Hazardous waste Material

14. Transportation Information

DOT (49 CFR 172)

Proper Shipping Name	Ground: Air:	Unrestricted Unrestricted
Hazard Class or Division:	Ground: Air:	Unrestricted Unrestricted
Identification Number:	Ground: Air:	None None
ΙΑΤΑ	All.	None
Proper Shipping Name: Class or Division: UN or ID Number:	Unrestricted Unrestricted None	
IMO		
Substance Marine pollutant Status Class	Not available Not available Not available	

Subsidiary Risk Label:	Not available
IMDG Code Page	Not available
UN Number	Not available

15. Regulatory Information

CA Proposition 65: No California Proposition 65 chemicals are known to be present.

16. Other Information

Estimated NFPA(R) Code: Health Hazard: Fire Hazard: Reactivity Hazard: Specific Hazard:	2 2 1 Does not apply
Estimated HMIS (R) Code: Health Hazard: Flammability Hazard:	2 2
Reactivity Hazards: Personal Protection:	1 See Section 8

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

DISCLAIMER:

The information contained within this MSDS applies only to the FastCap product to which the sheet relates. The information provided is based on our best knowledge at the time of issue.

The information contained within this MSDS is believed to be accurate and is given in good faith. However, no warranty is made, either express or implied, regarding its accuracy or any liability arising out of the use of the information herein or the product supplied.

When used in other preparations, formulations, or in mixtures, it is necessary to ascertain whether the classifications of the hazards have changed. The attention of the user is drawn to the possibility of creating other hazards when the product is used for purpose other than that for which it was recommended. In such cases, a reassessment may be necessary and should be made by the user.

This safety data sheet should only be used and reproduced in order that the necessary measures are taken relating to the protection of health and safety at work.

It is the responsibility of the handlers to pass on the totality of the information contained within this document to any subsequent person(s) who will come in to contact with, handle or use this product in any way.

They should check the adequacy of the information provided within this MSDS before passing it on to their customers/staff.