

N-1: Adhesives

Section N-1: Adhesives

Adhesives

Maverick Hardware

Adhesives

Section N-1: Adhesives

Titebond Original Wood Glue

Provides a strong initial tack and fast set up to reduce clamp time. Used for assembly gluing, edge and face gluing, as well as other applications. Easy clean up with water. Bonds wood, hardboard, high pressure laminates, and particleboard. Cream colored dries translucent.

Part #	Color	Size
FRTB-16	Cream	16 oz.
FRTB-G	Cream	Gallon



Titebond Extend Wood Glue

A slower setting version of Titebond Original Wood Glue. Useful in operations that require more time to align.

Part #	Size
FRTBE-G	Gallon



Titebond II Premium Wood Glue

The only leading brand one-part wood glue that passes the ANSI Type II water-resistance testing. Perfect for exterior wood projects and applications that are exposed to moisture. Strong initial tack. Easy water clean-up.

Part #	Size
FRTB2-16	16 oz.
FRTB2-G	Gallon



Titebond II Extend Wood Glue

A slower setting version of Titebond II Original Wood Glue. Useful in operations that require more time to align.

Part #	Size
FRTB2E-G	Gallon



Titebond III Ultimate Wood Glue

Is the most advanced wood glue available today. It combines the strength, sand ability, ease of use and water cleanup of PVA's (aliphatic resins) with the durability, open time and water-resistance of polyurethanes. Superior strength, longer open time, lower application temperature, resists solvents, heat and mildew, unaffected by finishes, water cleanup and non-toxic. FDA approved for indirect food contact. Sands easily without softening, is safer than traditional waterproof glues, ultimate in waterproof (Passes Type I water resistance). Ultimate in strength, 4,000 psi, ultimate in time, 10-minute open time, and ultimate in temperature down to 47 degree F.

Part #	Size
FRTB3-16	16 oz.
FRTB3-G	Gallon



Titebond Polyurethane Glue

A professional strength waterproof glue specifically formulated for multipurpose applications. In addition to its superior wood-to-wood performance it is ideal for metal, ceramic, plastic, HPL, Corain, stone, and other porous/nonporous materials. Is it ready-to-use and offers excellent sand ability and is unaffected by finishes. Twice as thick as traditional polyurethanes, it provides a no-run, no-drip glue line for more precise applications. Does not become brittle with age and will not expand or contract in the glue joint.

Part #	Size
FRP-12	12oz.



Speed Tape

FastCaps high quality adhesive in a peel and stick roll! Apply SpeedTape to your veneers and laminates, peel of the liner and stick it! If you have a peel and stick application, SpeedTape is the answer you are looking for! Available in 50' rolls.



Part #	Description
FCST.1.0X50	1" x 50' Roll
FCST.1.5X50	1.5" x 50' Roll
FCST.2.0X50	2" x 50' Roll
FCST.6.5X50	6.5" x 50' Roll

Adhesives

Glue-Bot

The only glue bottle that will not drip or spill. You will never have to clean up glue spills or drips again. Features easy squeeze bottle.



<u>Part #</u>	<u>Size/Description</u>
FCGB-16	16oz Glu-Bot
FCGB-04	4 oz. Glu-Bot
FCGB.LID-16	16 oz. Replacement Lid
FCGB.YOKERTIP-16	16 oz. Yoker Tips 5/pk
FCGB.BLADETIP-16	16 oz. Blade Tip 5/pk
FCGB.CAP-16	16 oz Replacement Caps Red
FCGB.LID-04	4 oz. Replacement Lid
FCGB.YOKERTIP-04	4 oz. Yoker Tips 5/pk
FCGB.BLADETIP-04	4 oz. Blade Tip 5/pk
FCGB.CAP-04	4 oz. Replacement Caps Red

Gorilla Glue

100% solvent free, polyurethane premium waterproof glue for indoor and outdoor use. Unaffected by extreme hot and cold temperatures and will not break down when exposed to rain or snow. Bonds all types of wood including pressure treated lumber. In addition it bonds stone, metals, ceramics, styrofoam and more. Leaves an invisible glue line that can be painted and stained, and is easily sanded. Only needs to be applied to one surface because it will foam to three times its size. Color: Goes on dark, dries neutral. Open time: 20 minutes.



<u>Part #</u>	<u>Size</u>
GORILLAGLUE-18	18 oz.

Empty Glue Bottles and Replacement Caps



<u>Part #</u>	<u>Description</u>
FRGB16	16oz. Glue Bottle
FRGBT	16oz. Replacement Tip



Roo Clear Melamine

Is a ready-to-use acrylic emulsion adhesive for the bonding of synthetic laminated board to timber, particleboard, MDF board, and other semi-porous surfaces. It is an excellent adhesive for a variety of laminates including melamine and vinyl coated board. Widely used in the furniture industry for assembly of laminated board with traditional fittings such as dowels, cams, staples, nails, and screws. Dries clear.



<u>Part #</u>	<u>Size</u>
RGM-16	16 oz.
RGM-G	Gallon

Breeze Tip

The breeze tip was developed as a more effective and efficient way to spread adhesive on solid surface countertops. This tool was conceived by a solid surface fabricator and named after his daughter Breezy. The Fastcap design team developed the idea further to save you time and expensive adhesive. It simply clips on to the end of a static mixing tip and the built in guide system allows you to easily spread a uniform film of adhesive every time.



<u>Part #</u>	<u>Description</u>
FCBREEZETIP-1/2"W/G	1/2" Breeze Tip W/Guide 10/pk
FCBREEZETIP-1"W/G	1" Breeze Tip W/Guide 10/pk

Roo Wood

High-Strength Wood Glue is especially formulated for bonding wood, wood composite, and other similar materials. Possesses excellent heat resistance, fast setting speed and good assembly time tolerance. It resists most solvents, is easily sandable, and emits no organic vapors, water based, user-friendly, environmentally safe. For best results, substrate surface temperatures should be between 50-80 degree F. All joints should be freshly machined and fit tightly. Apply enough glue to get minimal squeeze out when clamped or pressed. Clamp time of 4 hours at 70 degree F, is recommended. For best results, cure overnight before machining.



<u>Part #</u>	<u>Color</u>	<u>Size</u>
RGW-16	White	16 oz
RGW-G	White	Gallon
RGWY-G	Yellow	Gallon

Maverick Hardware

Adhesives

Hi Performer Advanced Bonding System

Kit includes: Gun, case, adhesive. Polyurethane hot melt technology is not new to the adhesive industry. In fact, polyurethane hot melts have been successfully utilized for many different applications for several years. They combine the positive attributes found in various, unique adhesive technologies and deliver them in a single product. Polyurethane hot melt adhesives outperform traditional hot melts, offer a faster set than yellow glues, and provide a more permanent, less brittle bond than super glues. In addition, this technology provides a strong, waterproof bond which reduces the need for clamping, bracing, and works on most common woodworking and construction materials.



Part #	Description
FR1341	Hi-Performer Kit
FR1301	30 Second Wood to Wood Bond
FR1311	60 Second Wood to Wood Bond
FR1321	MP75 Multi Purpose Adhesive

2-P10 Adhesive System

2P-10 is an industrial grade instant glue. It is triple distilled and acidically modified to work specifically with wood. Its greatest benefits are its speed and strength.

- Sets in 10 seconds - cures in 30 seconds
- Easy to sand within 60 seconds
- 2 year shelf-life guaranteed
- 4000 PSI tensile & shear
- Non clogging pin-cap
- Dries crystal clear



Part #	Description
FC2P10.KIT.2OZ	2P10 2.25 oz kit
FC2P-10.2.25OZ.JEL	2P10 2.25 oz jel
FC2P-10.2.25OZ.MED	2P10 2.25 oz medium
FC2P-10.2.25OZ.THICK	2P10 2.25 oz thick
FC2P-10.2.25OZ.THIN	2P10 2.25 oz thin
FC2P-10.10OZ.JEL	2P10 10 oz jel
FC2P-10.10OZ.MED	2P10 10 oz medium
FC2P-10.10OZ.THICK	2P10 10 oz thick
FC2P-10.ACT.12OZ	2P10 activator 12 oz
FC2P-10.ACT.2OZ	2P10 activator 2 oz
FC2P10.DEBONDER	2P10 debonder 2 oz
FC2P10.MICROTIP	2P10 microtip
FC2P10.PINCAP	2P10 pincap
FC2P10.SPR	Spray pump replacement
FC2P-10JEL TUBE 10oz	10 oz. Caulking Tube

Caulked N'Ready FCCAULKEDNREADY



The Caulked N'Ready fits on your belt, hangs on your pocket, and can be clipped to your workbench or truck.



SF-450 Heavy Duty Sub- Floor and Construction Adhesive



Is a premium heavy-duty grade adhesive for Glued-Floor Systems. Cold weather formula for easier extrusion and excellent adhesion in all weather conditions. Bonds dry, wet, frozen, and treated lumber to most building materials. Offers fast set and superior strength development. Also available in VOC compliant formula.

Part #	Description	Cs. Qty.
OSISF450-28	28oz. Cartridge	12



Titebond Heavy Duty Construction Adhesive



Titebond Heavy Duty Construction Adhesive is a versatile adhesive that exceeds the APA's AFG-01 specification. It is designed for a wide range of construction applications including wet, frozen and treated lumber. It is also ideal for metal, brick, concrete, ceramics and most large panel-type substrates.

Part #	Description
FR5261	10oz. Cartridge
FR5262	30oz. Cartridge

2-P10 Colorant System Adhesive System Colorant



The new colorant kit allows you to mix exactly the right tint of 2P-10 filler in seconds. This high tech colorant is specifically made to work with the 2P-10 system. Colorant is extremely permanent on all surfaces. The kit includes an instruction sheet, carrying case, 2P-10 Jel Adhesive (2.25 oz), pad to mix adhesive and colorant on, sticks for mixing ingredients together, and six colors for mixing. Individual colors are also available.



Part #	Description
FC2P10.COLORKIT	Color Kit
FC2P10.YELLOW	Yellow
FC2P10.BROWN	Brown
FC2P10.RED	Red
FC2P10.BLUE	Blue
FC2P10.BLACK	Black
FC2P10.WHITE	White

Adhesives

Acrylic Caulk With Silicone

Is a high quality water based caulk guaranteed for 40 years. Silicone has been added giving the caulk extra durability and adhesion. Because it is fast drying, it is ideal for professional painters and homeowners alike. Easy to apply and clean-up. Paints in 30 minutes. Ideal for caulking gaps and cracks along walls and baseboards; sealing air leaks around windows and doors, or prepping a room for painting.



Part #	Description	Cs. Qty.
OSIAC-AL	Almond 10 oz. Cartridge	12
OSIAC-CL	Clear 10 oz. Cartridge	12
OSIAC-GR	Gray 10 oz. Cartridge	12
OSIAC-WH	White 10 oz. Cartridge	12

100% Silicone Sealant

A 100% silicone rubber sealant that withstands the damaging effects of weather. Provides a watertight seal indoor or out. Ideal for HVAC applications. Withstands temperatures from -65 degree F (-54 degree C) to 450 degree F (232 degree C) and remains flexible. Adheres to glass, porcelain, ceramic tiles, and some plastics.



Part #	Description	Cs. Qty.
OSIS-CL	Clear 10 oz. Cartridge	12
OSIS-WH	White 10 oz. Cartridge	12

Permagrip 107 Hi Temp Aerosol Adhesive

A high temperature resistant, high performance grade contact adhesive in a flammable propellant. Very high strength adhesive formulated for the woodworking and marine industries. Its shear and peel strength makes it ideal for bonding high pressure laminates to various substrates and auto, RV and boat interiors. Fast dry times of 1 to 2 minutes and 5 to 10 minutes open time make this a very production efficient product. Times may vary due to temperature and humidity. Free of ozone depleting chemicals and free of CFC's. Self contained system affords portability not allowed by more traditional spray systems. Approximately 64 sq ft per pound coverage.



Part #	Description
HL107	17 oz aerosol can
HL107-38	38 lb disposable cylinder

Equipment for Permagrip 107



Part #	Description
HLGUN	Spray gun with tip
HLGUN-TIP-S	#6501 spray tip
HLHOSE-06	6' hose **
HLHOSE-09	9' hose **
HLHOSE-12	12' hose
HLHOSE-18	18' hose
HLHOSE-25	25' hose **
HLSV	Slitter valve **

** special order items only

Jumbo Sealant Applicator J-6

Professional heavy duty caulking applicator for large (quart) cartridges. Metal construction.



Part #	Description	Cs. Qty.
OSI-CG-J6	28 oz. Blue Professional	6

Chilton HD Sealant Application C-6

Professional, heavy-duty construction grade caulking applicator. High quality metal construction, designed to handle thick or stiff materials easily. Holds 1/10 gal. Cartridges.



Part #	Description
OSI-CG-C6	11 oz. Black/Yellow Heavy Duty

Skeleton Sealant Application W-12

Light to medium duty caulking applicator holds 1/10 gal. cartridges. Standard weight, metal construction. Not designed for high performance sealants.



Part #	Description	Cs. Qty.
OSI-CG-W12	11 oz. Blue Medium Duty	12

Maverick Hardware

Adhesives

Section N-1: Adhesives

Jowat

Medium viscosity hot melts. Good adhesive properties, especially to primed HPL. Good color and heat stability in the melt. Suitable for primed HPL, solid wood, veneer, PVC and resonated paper, specially designed for primed HPL.

Clean while hot by scraping with a spatula or when cold with Jowat cleaner (401.20)

We strongly recommend that any user of Jowalt products conduct its own testing.

Application temperature is 180 - 200° C (356 - 392° F)

Feed speed with roller application 18 - 60 m per minute (50 - 180 ft/min)

Feed speed with nozzle application 12 - 25 m per minute (35 - 75 ft/min)

<u>Part #</u>	<u>Description</u>	<u>Size</u>
JO288-60	Natural pellets	55 lb bag
JO288-61	White pellets	55 lb bag



Jowat Unfilled Cartridge

Medium viscosity hot melts with high heat resistance and good cold flexibility. Excellent color and heat stability in the melt. Hot melt for automatic edge banding, suitable for solid wood, veneer, PVC and resonated paper edgebands.

Clean while hot by scraping with a spatula or when cold with Jowat cleaner (401.20)

We strongly recommend that any user of Jowalt products conduct its own testing.

Application temperature is 180 - 200° C (356 - 392° F)

Feed speed with roller application 18 - 60 m per minute (50 - 180 ft/min)

Feed speed with nozzle application 10 - 40 m per minute (30 - 120 ft/min)

<u>Part #</u>	<u>Description</u>	<u>Size</u>
JO286-30	Natural cartridge	26 lb box



Jowat

High viscosity hot melts high heat resistance and good cold flexibility. Excellent color and heat stability in the melt. Hot melt for automatic edge banding suitable for solid wood, veneer, PVC and resonated paper edge bands. Also used for soft forming applications.

Clean while hot by scraping with a spatula or when cold with Jowat cleaner (401.20)

We strongly recommend that any user of Jowalt products conduct its own testing.

Application temperature is 190 - 210° C (374 - 410° F)

Feed speed with roller application 18 - 60 m per minute (50 - 180 ft/min)

Feed speed with nozzle application 10- 40 m per minute (30 - 120 ft/min)

<u>Part #</u>	<u>Description</u>	<u>Size</u>
JO280-90	Clear melt pellets	#55 bag
JO280-10	Natural pellets	#55 bag

